


# Mixing stations for 4 to 25 liter drums

237015-EM03P



← In operation with rev counter display set (opt)



← BKP-600-S2-x  
Drum holder device  
(optional)

Fully pneumatic mixing station offering extreme versatility in terms of safety and operational efficiency. Standard equipment includes a cowless propeller for high dispersion and product homogenization. Its extreme sturdiness allows for safe mixing at a fixed working height or even during intermediate phases for perfect incorporation of products that require it. Integrated station complete with adjustable drum locking device and safety sensors in series (intervention consent - drum presence).

## Mixing for

- 4 kg drums (approx. dimensions:  $\varnothing 21$  x h. 19 cm)
- 16 ÷ 25 kg mini drums (approx. dimensions:  $\varnothing 29.5$  x h. 43 cm)

## Equipment 237015-EM03P includes

- PMRD-015-V33 pneumatic agitator      Stainless steel
- Pneumatic elevator 230790
- Drum support base and locking brackets      Stainless steel

## Essential characteristics of equipment 237015-EM03P

- Centralized compressed air connection      G 1/2" (F)
- Max motor power (@ 6 bar)      1.5 HP
- Stall torque      5,6 Nm
- Motor power supply air      2 ÷ 6 bar
- Pneumatic lift stroke      600 mm
- Consumption at max power      1,3 m<sup>3</sup>/min
- Dissolution propeller      cowless 100 mm
- RPM:      20 - 3000
- Total shaft length (from flange surface)      510 mm

## Optional

- Versions with different power ratings
- Propellers for specific uses
- Rev counter set with display
- Pneumatically controlled safety drum holder (suitable for positioning drums complete with handling support)